

SKIPPER

Multi Repeater

CD401MR-SC

Operation and Installation Manual



SKIPPER Electronics AS
Enebakkveien 150
P. O. Box 151, Manglerud
0612 Oslo, Norway

www.skipper.no
Telephone: +47 23 30 22 70
E-mail: support@skipper.no
Co. reg. no: NO-965378847-MVA

Document no: **DM-R006-SC**
Rev: 2242
for sw version 1.6x
Date: 2022-09-26



CD401MR-SC

Operation and Installation Manual

Weitergabe sowie vervielfältigung dieser unterlage, verwertung und mitteilung ihres inhaltes nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu schadenersatz.

Toute communication ou reproduction de ce document, toute exploitation ou communication de ou son contenu sont interdites, sauf autorisation expresse. Tout manquement à cette règle est illicite et expose son auteur au versement de dommages et intérêts.

Copying of this document, and giving it to others and the use or communication of contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages.

Sin nuestra expresa autorización, queda terminantemente prohibida la reproducción total o parcial de este documento, así como su uso indebido y/o su exhibición o comunicación a terceros. De los infractores se exigirá el correspondiente resarcimiento de daños y perjuicios.

TABLE OF CONTENTS

Overview.	5
Terminology. Terms used in this manual	6
Units	6
Abbreviations	6
Introduction. The Multi Repeater	7
Chapter 1. Physical installation	8
The Dimming Inputs	9
Chapter 2. Setting up and using the Compact Multi Repeater Display	10
Principles	10
Runtime screens	10
Menu screens	10
Shifting screens	10
Activating the runtime screens	11
Menu Diagram	12
Setup of inputs	14
Changing of the baud rate	14
Demo mode	14
Master Reset (Factory Default Settings)	14
Chapter 3. Configuring the screens	15
Runtime screens	15
Accepted NMEA sentences	15
Configuration and operational screen	16
Configuring of screens	16
Depth	17
Speed	18
Distance	19
Heading	20
Rotation	21
Pitch and Roll	22
Wind	23
Temperature	25
Drive	26
Clock/UTC	27
Display Dimming Control	27
Auxillary	28

Error Handling	29
Chapter 4. Maintenance	30
Routine maintenance	30
Checking your version	30
Firmware upgrade	30
Mounting the Multi Repeater facing aft.	30
Appendix 1.	31
Specifications and mechanical drawing	31
System specification	31
Display	31
inputs/outputs	31
Mechanical dimensions	32
Appendix 2.	33
Accepted NMEA 0183 sentences Summary	33
output NMEA 0183 sentences Summary	35
Detailed description	36
Appendix 3.	44
Compact display CD401 options	44
Converting the CD401 system	45
Cabling CD401MR-SC vs. CD401MR-SB	46
Notes:	47

OVERVIEW.

Terminology

Terms, units and abbreviations used in this manual.

Introduction

This part introduces you to the elements of the Multi Repeater (MR) system.

Chapter 1 – Physical installation

Correct installation of the system will ensure problem free service for many years. This section explains the main steps to get your system working.

Chapter 2 – Setting up and using the Compact Multi Repeater display

The Compact Multi Repeater display is a flexible intuitive display allowing data to be displayed in a user friendly way. It is also a primary system and can be integrated into the navigation system as regulation stipulate. This chapter explains how to set up the unit.

Chapter 3 – Operation

Once the system is installed and operational, the user can change the screen to show the data of interest at any time. This section explains the operation of the system.

Chapter 4 – Maintenance

It is a good idea to verify your systems performance from time to time. This chapter describes how to check interfaces and other issues. In the event of malfunction, this is a good place to start for trouble shooting.

Appendix 1 – Specifications and drawings

Here you will find more details of how the system works and which factors are important to know when using it.

Appendix 2 – Accepted NMEA sentences

This section describes the inputs accepted by the Compact Multi Repeater display in this configuration

Appendix 3 - Other options with the CD401

The Compact can be used in a number of different system both as a repeater and a speed log. This section explains what is available and how to activate the options.

TERMINOLOGY. Terms used in this manual

UNITS

Unless otherwise stated, all values shown on the display are as follows:

Depth	Meters
Speed	Nautical miles per hour (knots)
Distance	Nautical miles (nm)
Heading	Degrees (0 – 359.9°)
Rotation	Degrees per minute (°/min)
Pitch and roll	Degrees (0 – 359.9°)
Wind	Nautical miles per hour (knots)
	Meter per seconds (m/s)
	Beaufort (Bft)
Temperature	Degrees Celcius (°C)
Speed revolutions	Revolutions per minute (rev/min)
Rudder angle	Degrees (0 – 359.9°)
Propeller pitch	Percentage of maximum (0 -100 %)
Clock /UTC	hh:mm (00:00 – 23:59)


ABBREVIATIONS

In addition the following symbols are used on the runtime screens:

T _p	Daily trip (in nm)
T _L	Total measured distance travelled (in nm)
°	Degrees
%	Percentage
←↑→↓	Direction

INTRODUCTION. The Multi Repeater


The SKIPPER Multi Repeater allow important values from a variety of systems to be displayed anywhere on the vessel. The CD401 Compact display is unique in its simple and flexible way to display vital data in almost all conditions, from no light to bright sunlight. In addition, it is classed to IP 56 allowing it to be mounted outside and used in any conditions. The unit is a standard 144 mm format allowing it to be mounted in tight spaces or overhead.



CHAPTER 1. Physical installation

The Multi Repeater CD401MR is a stand alone unit and does not require additional circuitry. It should be supplied by a 24 V (19 V-36 V) 25 W DC supply and the cabling of the system is as per diagram below. The unit is supplied with 2 m of cable (12 core). This can be extended without problem. Only the wires in use need extending.

Note: Mounting drawing is available in [Appendix 1](#).




NOTE

Compared to the CD401MR-SA/SB variants NMEA, A and B are switched , and NMEA out is replaced by NMEA 1 in this version (See appendix 3.)

THE DIMMING INPUTS

Pulses of at least 60 ms on the dimming up and dimming down cables will cause the dimming to change by one level. The inputs are optocoupled and therefore require an external voltage to operate, (5 Volt -24 Volt (Typically 5/12/24 Volt)).



CHAPTER 2. Setting up and using the Compact Multi Repeater Display

PRINCIPLES

The Compact Multi Repeater Display is a flexible dot matrix LED display designed to display navigation data. The Multi Repeater can be user programmed to show most kinds of numerical data from NMEA messages. The Compact has three user definable alphanumeric displays, each allowing up to 4 lines to be displayed.

RUNTIME SCREENS

The Compact Display starts up in runtime mode. By pressing the MENU button, the preset runtime screens can be selected. The unit can be dimmed in any of the runtime screens using the UP (↑) and DOWN (↓) buttons.

MENU SCREENS

To change the setup of the Multi Repeater, the user must simultaneously press MENU and SET buttons. This will give access to a menu system allowing the user to scroll up and down the sub menus and functions using UP and DOWN, and SET button to select. To move back and up a menu, the MENU button must be pressed. The middle underlined line is the selected line. The other lines are dimmed.

The menu structure is shown in the [MENU DIAGRAM](#).




Press both MENU and SET buttons to activate the menus. Press and hold MENU to return to runtime screen.

SHIFTING SCREENS

The system can be made to shift, with a five second period, between the activated screens. Pressing MENU will pause this function, and holding MENU will reactivate it.


ACTIVATING THE RUNTIME SCREENS


The system has three user preset runtime screens (SCR1, SCR2, SCR3). The Screen Menu allows the user to configure and choose which runtime screens to be included in normal operation. UP and DOWN buttons will scroll to the available screens. By using the SET button, the user can control each individual screen to ON, OFF or SHIFTING. Screens set to ON are available to be displayed by pressing the MENU button. Screens set to OFF will not be displayed. Screens set to SHIFTING will be shown on the display periodically. Each shifting runtime screen will be displayed for 5 seconds.



If any screens are configured to SHIFTING, these selected screens will automatically start displaying periodically. The shifting of these preset runtime screens are stopped if the MENU button is pressed in runtime mode. By holding down the MENU button longer, the shifting will be started again.

MENU DIAGRAM





SETUP OF INPUTS

The system will allow many NMEA formats to be displayed. No setup is required. The system has 2 input channels, both of these may be used.

CHANGING OF THE BAUD RATE

The NMEA (IEC61162-1) standard is 4800 baud. Some vessels run with higher baud rates. 4800, 9600, 19200, 38400, 57600 and 115200 baud rates can be selected in the baud screen of the setup menu.

DEMO MODE

A demo mode is available, and can be activated with MENU button in the diagnostics menu. Three modes are available.

- **Mode 1** is a dynamic demo mode taking the present values as the start point and slowly varying all the available values.
- **Mode 2** is a static mode taking the present values and keeping them active.
- **Mode 3** is a **fixed speed** longitudinal 5 kn, transversal 1 kn.

When the demo mode is active, alarms will be disabled, and the screen will indicate the demo state with a blinking S in the upper right corner. The user can turn off the demo mode from the demo screen, or by recycling the power. The demo mode will turn off automatically after 10 hours.

MASTER RESET (FACTORY DEFAULT SETTINGS)

The factory default settings can be restored by performing the following operations:

1. Select CODE in diagnostic (DIAG) menu.
2. Press the SET button (**Note:** Do not change code value).

The unit will now restart with factory default settings.



CHAPTER 3. Configuring the screens

RUNTIME SCREENS

The unit starts up in runtime mode. By pressing the MENU button, the preset runtime screens (SCR1, SCR2, SCR3) can be selected. The unit can be dimmed in any of the runtime screens using the UP (↑) and DOWN (↓) buttons. If Trip/Total are selected as a displayed parameter, they can be toggled using the SET button. If wind speed is selected as a displayed parameter, the unit can be toggled between knots, m/s, or Beaufort using the SET button. The Set button is used to reset the Trip counter if Trip Screen is displayed and the Multi Repeater is connected to a SKIPPER EML 224 system or a DL850 270 kHz system.



INFO Screen



TRIP Screen

ACCEPTED NMEA SENTENCES

When using the Compact Display as a Multi Repeater, the display could be user programmed to show the most commonly used NMEA 0183 (IEC61162) messages for:

Depth	Below surface, keel and transducer
Speed	Over ground and through water (longitudinal, transverse, aft and relative)
Distance	Total/trip for both ground and water
Heading	True, magnetic and relative
Rotation	Rate of turn and direction
Pitch and roll	In degrees
Wind	Speed and direction (true, magnetic and relative)
Temperature	Water and air
Drive	RPM (Revolutions Per Minute), propeller pitch and rudder position
Clock	UTC (Universal Time Coordinated), local time and Expected Time of Arrival (ETA)
Dimming	Display dimming
Auxillary	User defined NMEA messages

A summary of supported NMEA sentences is listed in [Appendix 2](#).

CONFIGURATION AND OPERATIONAL SCREEN

The programming of parameters to show on the screen is very flexible. It is advise to add leading text before the parameters and not mixing too many different messages. A typical configuration is to show two related parameters on the screen simultaneously with leading text. Arrows are added to some parameters for better readability. Press MENU and SET button simultaneously to enter the screen menus, select CONFG and then select wanted screen menu (CFG1, CFG2 or CFG3) to start to configure wanted screen menu. See chapter 2 ["Setting up and using the Compact Display"](#) on how to program the display to show wanted information on the screen.

CONFIGURING OF SCREENS

The 3 user programmable screen menus can be set up using the Config (CONFG) menu. This submenu allows the user to select one of the three screen menus, and on entering the Config screen menu, the user can change the data type to be displayed in each of the 4 screen menu's positions. UP (↑) and DOWN (↓) will change the data type, SET will move to the next screen menu position.



Placing text (TXT) in the bottom 4th line or 3rd and 4th line will cause the data to spread out showing fewer data points. The system will not allow you to mix speed data from different sources on the same screen. Having two text (TXT) lines after each other will also rearrange the positioning. (See examples on next page).

The non-active parameters will continue showing the dimmed present data, when not selected. Some combinations of data are not allowed, as they may cause confusion. These will be automatically corrected. Note that the leading text is identical for some data, and information about talkers are ignored. Regulations require the user to be able to identify which data they are looking at. This can be achieved by using the TXT function or a sticker on the unit.

Depth

The NMEA sentences DPT, DBS, DBT, DBK and PSKPDPT are all supported for receiving information about the depth. The use of the DPT sentence is recommended when available. Depth values in feet and fathoms (from DBK, DBT and DBS) are converted to meters. The screen will display either DEPTH-S (depth below surface), DEPTH-T (depth below Transducer) or DEPTH-K (depth below keel) depending of the received sentences (DBS, DBT or DBK) or the offset value in DPT. The proprietary sentence PSKPDPT is able to distinguish between both transducer location and channel number. The transducer location is indicated by an arrow in the text line. The channel number is selected by parameter PDPT1, PDPT2 or PDPT3 and is written in the text line as DPT1, DPT2 or DPT3 respectively for each channel. The parameter name PDPT will ignore channel number and is written in the text line as DEPTH.

The depth is always displayed in meters. Depth values below 10 meters are displayed with 2 decimals, depth values between 10 and 100 meters are displayed with 1 decimal and depth above 100 meters are displayed without decimals.

Maximum depth value to be displayed is 9999 meters.

**Config.
screen:**



**Runtime
screen:**



Speed

The NMEA sentence VBW is supported for receiving information about the speed through water and speed over ground (bottom) for longitudinal, transverse and transverse aft. The NMEA sentences VHW and VTG are supported for receiving information about relative speed.

- An arrow, indicating the direction, is added in front of the value for speed values from the NMEA sentences VBW. In the case of 2 VBW messages from separate SOG and STW sensors, both can be used as long as the unused fields are left blank. (DL21, EML and SL1200 etc.)
- The relative **speed through water** is fetched from the NMEA sentence VHW.
- The relative **speed over ground** is fetched from the NMEA sentence VTG.
- Speed value in km/h is converted to knots if speed value in knots is not available.
- Relative speed is displayed without arrows.
- All speed values are displayed in knots with either one or two decimals depending of the configured parameter to display. STW2L, STW2T, SOG2L and SOG2T will always display speed below 10 knots with two decimals and speed from 10 knots and above with one decimal. All other speed parameters are displayed with one decimal (see the detailed description of the parameters in [Appendix 2](#)). Maximum speed value to be displayed is +/- 99.9 knots.

**Config.
screen:**



**Runtime
screen:**



T

Distance

The NMEA sentence VLW are supported for receiving information about distances. The Trip/Total parameters for either water distance or ground distance can be toggled using the SET button.

The distance values are always displayed in nautical miles and the value will wrap around after reaching the maximum value of 99999. Total/trip values below 10 are displayed with two decimals, values between 10 and 1000 with one decimal and values above 1000 are displayed with no decimals.

Configuration screen:



Runtime screen:



Heading

The NMEA sentences VHW, VTG, THS, HDT, HDM and HDG are all supported for receiving information about the heading. It is recommended to use THS instead of HDT, and HDG instead of HDM when available. The deviation and variation parameters in HDT are ignored.

If the same heading parameter is received from different talkers, the heading parameter will be prioritized as shown below:

1. Gyro, north seeking (HE).
2. GPS (GP).
3. Compass, magnetic (HC).
4. Others.

An arrow is added on the text line to indicate which direction the bow turns. If no change in heading from previous value, no arrow is displayed.

The heading value is always displayed with one decimal. Legal range for the heading to be displayed, are values in the range from 0 to 359.9°.

**Config.
screen:**



**Runtime
screen:**



Direction of turn is to port.



Direction of turn is to starboard.



No change in heading since last message.

Rotation

The NMEA sentence ROT is supported for receiving information about the rotation. A steady arrow is added on the text line to indicate which direction the bow turns.

- A positive received value indicates that bow turns to starboard and an arrow to the right is displayed.
- A negative received value indicates that bow turns to port and an arrow to the left is displayed.
- A value of zero indicates no rotation and no arrow is displayed.

Values below 99.9 are displayed with one decimal. Values above 100 are displayed with no decimals. Maximum value to display is +/- 999°/min.

Configuration screen:



Runtime screen:



Pitch and Roll

The NMEA sentence XDR, version B is supported for receiving information about the pitch and roll.

- A positive received value for pitch indicates that the bow is up and negative if bow is down.
- A positive received value for roll indicates that port is up and starboard is down, a negative value indicates that starboard is up and port is down.

Values below 10 degrees are displayed with two decimals and values above 10 degrees with one decimal. Maximum value to be displayed is +/- 359.9°.

Configuration screen:



Runtime screen:



Wind

The NMEA sentences MWV, VWR, VWT and MWD are all supported for receiving information about the wind speed and direction. MWV is recommended instead of VWR and VWT, when available. All wind speed units are accepted (knots (N), m/s (M) and km/h (K)) and converted to wanted speed units to display on the screen. Speed units on the display may be toggled between kn (knots), m/s and Bft (Beaufort) by pressing the SET-button.

A graphical representation of the wind angle is displayed if the following parameters are selected:

- TXT must be selected for the first two parameters.
- One wind angle must be selected.
- Corresponding wind speed from the same NMEA sentence could be selected. Otherwise TXT must be selected.
- The wind angle is represented by an arrow on the screen.

See chapter 2 ["Setting up and using the Compact Display"](#) for details how to set up the screen.

The range of values to be displayed, are:

- Speed: 0 - 99.9 knots.
- Heading: 0 – 359.9°.

Wind, (continued from previous page):

Config.
screen:



Runtime
screen:




SET button has been pressed for toggling the speed units to m/s.

Configuration
screen:



Graphical
representation



Runtime
screen:



SET button has been pressed for changing between knots, m/s and Beaufort units.

Temperature

The NMEA sentences MTA, MTW and MDA are supported for receiving information about the air (MTA or MDA) and water (MTW) temperatures. Air temperature from MDA is used if data from MTA is not available.

Temperatures are displayed in degrees Celsius. Values below 10 degrees are displayed with two decimals and values above 10 degrees with one decimal. The maximum/minimum temperatures to be displayed are +/- 99.9°C.

Configuration screen:



Runtime screen:



Drive

- The NMEA sentence RPM is supported for receiving information about the speed revolutions (rev/min) and propeller pitch (% of maximum).
- The NMEA sentence RSA is supported for receiving information about the rudder angle.

The speed revolution values below 999.9 is displayed with one decimal and values above 1000 is displayed without decimals. Propeller pitch values below 10 % are displayed with two decimals and values above 10 % with one decimal.

- Max./min. value to be displayed for speed revolution is +/- 9999 rev/min.
- Max./min. value to be displayed for propeller pitch is +/- 100 %.
- Max./min. value to be displayed for rudder angle is +/- 359.9°.

Configuration screen:



Runtime screen:



Clock/UTC

The UTC is fetched from either of the NMEA sentences ZTG, ZDA, GGA or RMC, prioritized in the same order. The NMEA sentences ZDA is used for receiving information about the local time. The NMEA sentences ZTG is used for receiving information about expected time of arrival. Maximum offset for displayed time of "Expected Time of Arrival" is 24 hours. All time values are displayed with the format hh:mm, where hh are hours and mm are minutes.

**Config.
screen:**



**Runtime
screen:**



Local time is
UTC – (1h 30 min).

Expected Time of
Arrival is UTC +
(20h 45 min).

Display Dimming Control

The brightness of the display can be controlled by the NMEA sentence DDC. Note that the brightness also can be controlled by buttons on the display and remote dimmer control (IR30DIM). Both the brightness percentage and display dimming preset are supported in the NMEA sentence DDC ([see Appendix 2](#)).

ERROR HANDLING

All parameters within each NMEA sentences are checked for checksum, legal range, validity and timeout.

Bad checksum (- - - -)

If the checksum field (*hh) is present, the value is checked. The screen will indicate bad checksum by displaying minus signs instead of the value (- - - -). If no checksum field is present, no checking is performed.

Illegal range and validity (. . . .)

Some values must be within a range. If a value is out of range, the following exception is performed:

- **Wrap around:** The displayed value will start from zero again after reaching the maximum/minimum value (trip values, only).
- **Limited value:** The maximum or minimum value will be displayed (speed and temperature values).
- **Illegal value:** The value has no meaning (ex. heading values above 360°). The screen will indicate illegal value by displaying dots instead of the value (. . .).

A Null field is a field in the NMEA sentence without any character between two delimiter characters. A Null field indicates that the value is unreliable or not available. The screen will indicate a Null field by displaying dots instead of the value (. . . .) if no value is received within the timeout timeframe.

Some parameters has a status parameters associated with them (A = data valid, V = data invalid). The screen will indicate an invalid parameter by displaying dots instead of the value (. . . .) if no new valid value is received within the timeout timeframe.

Timeout (ERROR)

The timeout value for each parameter within each NMEA sentence is 10 seconds. The screen will indicate timeout by displaying an error message (ERROR) if no new value is received within the timeout timeframe.

CHAPTER 4. Maintenance

ROUTINE MAINTENANCE

No maintenance is required. The screen can be cleaned with a soft cloth.

CHECKING YOUR VERSION

If the info screen is activated on the run screens, the system type and firmware version can be read from there. Otherwise the same screen can be obtained in the diagnostics menu. The system type will be one of the following:

CD401E1	Compact display EML 1 Axis.
CD401E2	Compact display EML 2 Axis.
CD401EB	Compact display EML 2 Axis backwards.
CD401LR	Compact display Log Repeater.
CD401MR	Compact display Multi Repeater.
CD401MB	Compact display Multi Repeater backwards.

The system will be locked to one of these setups, but can be changed to one of the other systems (with an additional cost) using a code ([see Appendix 3](#)).

FIRMWARE UPGRADE

The system is undergoing continuously improvements, and periodically new firmware will be released. A chip can be supplied (with an additional cost) with the new software. This is changed by removing the backplate of the Compact display.

MOUNTING THE MULTI REPEATER FACING AFT.

The Compact Display could also be set up to operate in "Multi Repeater, Backwards" mode. In this mode all speeds are in opposite direction. See [Appendix 3](#) on how to change the system setup. The parameters in "Multi Repeater, Backwards" mode will be replaced according to the following:

STWWL = - STWWL	SOGBL = - SOGBL
STWWT = - STWWA	SOGBT = - SOGBA
STWWA = - STWWT	SOGBA = - SOGBT

APPENDIX 1.

SPECIFICATIONS AND MECHANICAL DRAWING

SYSTEM SPECIFICATION

Power Supply	DC: 19 - 36 V/25 Watt.
Display	28 x 30 pixel, Alphanumeric LED (red). With dimming.
Languages	English.
Accessories	Dimming control.
Classification	IMO MED B.
Service	Available in most major harbours, world-wide through extensive dealer network. See www.skipper.no for further information.


DISPLAY

Weight (display)	1.3 kg.
Cable length	2 m (can be extended).
Compass safe distance (min)	30 cm.
User adjustable screens	3
Parameters per screen	2 with text, 3 with single text line.

INPUTS/OUTPUTS

Outputs	1 x NMEA (IEC61162-1) (2007).
Inputs	2 x NMEA (IEC61162-1) (2007).
	External dimming (up and down pulses).

MECHANICAL DIMENTIONS



APPENDIX 2.
ACCEPTED NMEA 0183 SENTENCES SUMMARY

	NMEA Sentence	Description	Parameter Name	Screen name
Depth	DPT	Water Depth in meters	DPT	DEPTH-K DEPTH-T DEPTH-S
	DBK	Water Depth below Keel in meters	DBK	DEPTH-K
	DBT	Water Depth below Transducer in meters	DBT	DEPTH-T
	DBS	Water Depth below Surface in meters	DBS	DEPTH-S
	PSKPDPT	SKIPPER proprietary depth sentence	PDPT	DEPTH-K DEPTH-T DEPTH-S
		SKIPPER proprietary depth sentence for channel 1	PDPT1	DPT1-K DPT1-T DPT1-S
		SKIPPER proprietary depth sentence for channel 2	PDPT2	DPT2-K DPT2-T DPT2-S
		SKIPPER proprietary depth sentence for channel 3	PDPT3	DPT3-K DPT3-T DPT3-S

	NMEA Sentence	Description	Parameter Name	Screen name
Speed	VBW	Longitudinal Water Speed STWWL will have one decimal for all speed values STW2L always display speed below 10 knots with two decimals and speed from 10 knots and above with one decimal.	STWWL STW2L	STW
		Transverse Water Speed STWWT will have one decimal for all speed values STW2T always display speed below 10 knots with two decimals and speed from 10 knots and above with one decimal.	STWWT STW2T	STW
		Transverse Water Speed, Aft	STWWA	STW
		Longitudinal Ground Speed SOGBL will have one decimal for all speed values SOG2L always display speed below 10 knots with two decimals and speed from 10 knots and above with one decimal.	SOGBL SOG2L	SOG
		Transverse Ground Speed SOGBT will have one decimal for all speed values SOG2T always display speed below 10 knots with two decimals and speed from 10 knots and above with one decimal.	SOGBT SOG2T	SOG
		Transverse Ground Speed, Aft	SOGBA	SOG
	VHW	Speed Through Water in knots, relative	STW-R	STW-R
	VTG	Speed over Ground in knots, relative	SOG-R	SOG-R
	XDR	Water Speed direction, displayed as arrow on screen	-	-
Distance	VLW	Water-track Distance since reset	TRIPW	TRIPW
		Water-track Total distance	TOTLW	TOTLW
		Bottom-track Distance since reset	TRIPB	TRIPB
		Bottom-track Total distance	TOTLB	TOTLB
Heading.	VHW	Heading, degrees, true	HDW-T	HDG.T
		Heading, degrees, magnetic	HDW-M	HDG.M
	VTG	Heading (Course Over Ground), degrees, true	COG-T	COG.T
		Heading (Course Over Ground), degrees, magnetic	COG-M	COG.M
	THS	Heading, degrees, true	THS	HDG.T
	HDT	Heading, degrees, true	HDT	HDG.T
	HDM	Heading, degrees, magnetic	HDM	HDG.M
	HDG	Heading, degrees, magnetic	HDG	HDG.M
Rotation	ROT	Rate of Turn in degrees/minute	ROT	ROT
Pitch and roll	XDR	Pitch	PITCH	PITCH
		Roll	ROLL	ROLL

	NMEA Sentence	Description	Parameter Name	Screen name
Wind	MWV	Wind angle, Theoretical (True)	MWVAT	WIND-T
		Wind angle, Relative	MWVAR	WIND-R
		Wind speed in knots	MWVNT	WIND-T
		Wind speed in m/s	MWVMT	WIND-T
		Wind speed in Beaufort	MWVBT	WIND-T
		Wind speed in knots	MWVNR	WIND-R
		Wind speed in m/s	MWVMR	WIND-R
		Wind speed in Beaufort	MWVBR	WIND-R
	VWR	Wind angle, Relative	VWR-A	WIND-R
		Wind speed in knots	VWR-N	WIND-R
	VWT	Wind angle, True	VWT-A	WIND-T
		Wind speed in knots	VWT-N	WIND-T
	MWD	Wind angle, True	MWD-T	WIND-T
		Wind angle, Magnetic	MWD-M	WIND.M
		Wind speed in knots	MWD-N	WIND
Temp.	MTA, MDA	Air Temperature in degree Celsius	ATEMP	AIRTEMP
	MTW	Water Temperature in degree Celsius	WTEMP	W.TEMP
Drive	RPM	Revolutions / min	RPM	RPM
		Propeller Pitch (% of maximum)	PPTCH	P.PITCH
	RSA	Rudder Sensor Angle	RSA	RUDDER
Clock/ UTC	ZTG, ZDA, GGA, RMC	UTC (hh:mm)	UTC	UTC
	ZDA	Local Time (hh:mm)	LOC	LOC
	ZTG	Expected Time of Arrival (UTC) (hh:mm)	ETA	ETA
Display dimming	DDC	Display Dimming Control		
Auxillary	Defined by proprietary NMEA sentence	User defined message 1 (Auxillary 1)	AUX1	Defined by proprietary NMEA sentence
		User defined message 2 (Auxillary 2)	AUX2	
		User defined message 3 (Auxillary 3)	AUX3	
		User defined message 4 (Auxillary 4)	AUX4	

OUTPUT NMEA 0183 SENTENCES SUMMARY

	NMEA Sentence	Description
Trip reset	PSKPRSTT	Reset Trip counter on EML and Doppler systems, triggered from a long press on 'SET' on the Trip reset runtime screen


The System will repeat the inputs from input 1 to the single output. Input 2 will not be repeated.

Speed:

**Parameter
name**

Dual Ground/Water Speed


\$--VBW,x.x, x.x, A, x.x, x.x, A, x.x, A, x.x, A*hh<CR><LF>



* Speed parameters STW2L, STW2T, SOG2L and SOG2T are always displayed with 2 decimals for speed values below 10 knots and with 1 decimal for speed values from 10 knots and above.


Water Speed and Heading

\$--VHW, , , , x.x, N, x.x, K*hh<CR><LF>




Course Over Ground and Ground Speed

\$--VTG, , , , x.x, N, x.x, K*hh<CR><LF>



Speed direction

\$VMXDR,A,x.x,D,SPDD*hh<CR><LF>



Distance:

**Parameter
name**

Dual Ground/Water Speed

\$--VLW, x.x, N, x.x, N, x.x, N, x.x, N*hh<CR><LF>

Ground distance since reset	TRIPB
Total cumulative ground distance	TOTLB
Water distance since reset	TRIPW
Total cumulative water distance	TOTLW

Note: All distance values must be specified in nautical miles.

Heading:

**Parameter
name**

Water Speed and Heading

\$--VHW, x.x, T, x.x, M, , , , *hh<CR><LF>

Heading, degrees magnetic	HDW-M
Heading, degrees true	HDW-T

Course Over Ground and Ground Speed

\$--VTG, x.x, T, x.x, M, , , , *hh<CR><LF>

Course over ground, degrees magnetic	COG-M
Course over ground, degrees true	COG-T

True Heading and Status

\$--THS, x.x, a*hh<CR><LF>

Mode indicator (see Note)	
Heading, degrees true	THS

Note: The Mode indicator is ignored

Heading True

\$--HDT, x.x, T*hh<CR><LF>

Heading, degrees true	HDT
-----------------------	-----

Heading Magnetic

\$--HDM, x.x, M*hh<CR><LF>

Heading, degrees magnetic	HDM
---------------------------	-----

Heading, Deviation and Variation

\$--HDG, x.x, , , , *hh<CR><LF>

Magnetic sensor heading, degrees	HDG
----------------------------------	-----

Rotation:

**Parameter
name**

Rate Of Turn

\$--ROT, x.x, A*hh<CR><LF>


Status: A=data valid, V=data invalid	
Rate of turn ($^{\circ}$ /min), "-" = bow turns to port	ROT

Pitch and Roll

Parameter
name

Transducer Measurements

\$--XDR, a, x.x, D, PTCH, a, x.x, D, ROLL*hh<CR><LF>




Wind:

Parameter
name


Wind Speed and Angle

\$--MWV, x.x, a, x.x, a, A*hh<CR><LF>




Relative Wind Speed and Angle

\$--VWR, x.x, a, x.x, N, x.x, M, x.x, K*hh<CR><LF>



True Wind and Speed Angle

\$--VWT, x.x, a, x.x, N, x.x, M, x.x, K*hh<CR><LF>



<u>Wind:</u>	Parameter name
Wind Direction and Speed	
\$--MWD, x.x, T, x.x, M, x.x, N, x.x, M*hh<CR><LF>	
Wind speed, m/s	MWD-N
Wind speed, knots	
Wind direction, 0 to 359 degrees Magnetic	MWD-M
Wind direction, 0 to 359 degrees True	MWD-T

<u>Temperature:</u>	Parameter name
Air Temperature	
\$--MTA, x.x, C*hh<CR><LF>	
Temperature, degree C	ATEMP
Meteorological Composite	
\$--MDA, , , , , x.x, C, , , , , , , , , , *hh<CR><LF>	
Air temperature, degree C	ATEMP

Water Temperature	
\$--MTW, x.x, C*hh<CR><LF>	
Temperature, degree C	WTEMP

<u>Drive:</u>	Parameter name
Revolutions	
\$--RPM, , , x.x, x.x, A*hh<CR><LF>	
Status: A=data valid, V=data invalid	
Propeller pitch, % of max, ”-”=astern	PPTCH
Speed, revolutions/min, ”-” counter clockwise	RPM

Rudder Sensor Angle	
\$--RSA, x.x, A, , hh<CR><LF>	
Status: A=data valid, V=data invalid	
Rudder sensor	RSA

<u>Clock / UTC</u>		Parameter name
UTC & Time to Destination Waypoint		
\$--ZTG, hhmmss.ss, hhmmss.ss,*hh<CR><LF>		
Time-to-go (max 24 h)		ETA
UTC of observation		UTC
Time & Date		
\$--ZDA, hhmmss.ss, , , , x.x, x.x*hh<CR><LF>		
Local zone minutes, 00 to +59		LOC
Local zone hours, 00 to +/- 13		
UTC of observation		UTC
Global Positioning System Fix Data		
\$--GGA, hhmmss.ss, , , , , , , , , , *hh<CR><LF>		
UTC of position		UTC
Recommended Minimum Specific GNSS Data		
\$--RMC, hhmmss.ss, , , , , , , , , , *hh<CR><LF>		
UTC of position		UTC

Display Dimming:

Display Dimming Control	
\$--DDC, a, xx,*hh<CR><LF>	
Brighthness Percentage:	00 (min) to 99 (max)
Display Dimming Preset:	D = Day time setting (max)
	K = Dusk setting
	N = Nighth time setting
	O = Backlighth off setting (min)

Trip Reset:

Trip Reset counter	
\$PSKPRSTT,*hh<CR><LF>	

APPENDIX 3.

COMPACT DISPLAY CD401 OPTIONS

The Compact Display can be set up for one of the following systems:

LR	Speed Repeater	Backplate with 2m 12 core cable
MR	Multi Repeater	Backplate with 2m 12 core cable
MB	Multi Repeater Backwards	Backplate with 2m 12 core cable
E1 (EML124 Compact)	EML. Single axis STW. Control unit	Backplate with 10m 17 core cable. With Electronic unit JB60CD
E2 (EML224 Compact)	EML. Dual axis STW. Control unit	Backplate with 10m 17 core cable. With Electronic unit JB60CD
EB (EML224 Compact)	EML Dual axis STW. Control unit. Backwards	Backplate with 10m 17 core cable. With Electronic unit JB60CD
D1 (DL1 Compact)	DL1. Single axis STW. Control unit	Backplate with 10m 17 core cable. With Electronic unit JB60CD
CU (DL1 Multi)	DL1 Multi. Single axis STW Control Unit	Backplate without cable. LAN communication with Electronic unit JB70D1

- **Speed Repeater:** A simple repeater for speed in single and dual axis and trip. Limited functionality.
- **Multi Repeater:** A comprehensive repeater for many of the most common used NMEA messages. Functions also for user defined messages.
- **Multi Repeater Backwards:** As above, but the speeds are shown in opposite direction.
- **Single Axis EML:** Primary display for EML224 Single axis Compact speed logs showing longitudinal speed values produced by the sensor.
- **Dual Axis EML:** Primary display for EML224 Dual axis Compact speed logs showing both longitudinal and transverse speed values produced by the sensor.
- **Dual Axis EML Backwards:** Primary display for EML224 Dual axis Compact speed logs showing both longitudinal and transverse speed values produced by the sensor, but can be connected to an external switch for showing the speeds in opposite direction.
- **Single Axis DL1 Compact:** Primary display for DL1 Single axis Compact speed logs showing longitudinal speed values produced by the sensor.
- **Single axis DL1 Multi** The same electronics is used for the CD402CU-SC.

CONVERTING THE CD401 SYSTEM

A multi repeater CD401MR can be converted to CD401MB by entering a code. Code is available using the CODE page in the DIAG menu. On this menu, the serial number is displayed, and the new code can be purchased from the SKIPPER retailer.

Code to be entered into the CODE page by using the arrow buttons.

Please note that the cabling is different for repeaters and speed logs, so it is not possible to convert a repeater to EML224 or DL1 display without replacing the back plate.

NOTE: It is important to note that pay option codes are unique for each individual unit and will not work on other units.



DIAG menu




CODE page

CABLING CD401MR-SC vs. CD401MR-SB

CD401MR-SB. SW-1.20

1 NMEA Input. 2 NMEA Outputs.

Output function to calculate current, or repeat NMEA input.




CD401MR-SC. SW 1.62

2 NMEA Inputs. 1 NMEA Output.

Output only repeats NMEA 1 input. No menu with calculation of current.

NMEA, A(-) and B(+) are switched



This image shows a full page of primary-ruled paper. It features ten sets of horizontal dashed lines, each set consisting of three parallel lines. These lines are evenly spaced vertically across the entire page, providing a guide for letter height and placement in handwriting practice. The background is white, and there are no margins or other markings present.

SKIPPER

SKIPPER Electronics AS
Enebakkveien 150
P. O. Box 151, Manglerud
0612 Oslo, Norway
www.skipper.no

Telephone: +47 23 30 22 70
Telefax: +47 23 30 22 71
E-mail: support@skipper.no
Co. reg. no: NO-965378847-MVA